

# AMIBIOS HIFLEX SETUP UTILITY -VERSION 1.07

## Standard

Floppy Drive A	Not Installed										
Floppy Drive B	1.44 MB 3.5"										
		TYPE	SIZE	CYLN	HEAD	WPCOM	SEC	LBA MODE	BLK MODE	PIO MODE	32BIT MODE
Pri Master	:	User				0		Off	Off	Auto	On
Pri Slave	:	Not Installed									
Sec Master	:	Not Installed									
Sec Slave	:	Not Installed									
Boot Sector Virus Protection		Disabled									

## Advanced

Bootup Sequence	C:.,A:.,CDROM:
Boot From SCSI/IDE	IDE
Fast GateA20	Enabled
Floppy Drive Swap	Disabled
PS/2 Mouse Support	Disabled
System Keyboard	Present
Primary Display	VGA/EGA
Password Check	Setup
OS/2 Compatible Mode	Disabled
Internal Cache	WriteBack
External Cache	Enabled
System BIOS Cacheable	Enabled
C000, 32k Shadow	Enabled
C800, 16k Shadow	Disabled
CC00, 16k Shadow	Disabled
D000, 16k Shadow	Disabled
D400, 16k Shadow	Disabled
D800, 16k Shadow	Disabled
DC00, 16k Shadow	Disabled

## Advanced Chipset

Memory Hole	Disabled
DRAM Timing Setting	Auto
EDO:FP Read Burst Timing	x222:x333
DRAM Write Burst Timing	x333
SRAM CAS# Latency	3
SRAM RAS# Timing	3:5:8
TypeF DMA Buffer Control1	Disabled
TypeF DMA Buffer Control2	Disabled
Peer Concurrency	Enabled
USB Function Enable	Disabled
USB Keyboard Support	Enabled

## Power Management Setup

Disabled

## PCI/Plug and Play Setup

Plug and Play Aware O/S	YES
PCI IRQ Priority Auto Settings	YES
Assign IRQ to PCI VGA Card	YES
PCI VGA Palette Snoop	Disabled
OffBoard PCI IDE Card	Auto
IRQ3	PCI/PnP
IRQ4	PCI/PnP
IRQ5	PCI/PnP
IRQ7	PCI/PnP
IRQ9	PCI/PnP
IRQ10	PCI/PnP
IRQ11	PCI/PnP
IRQ14	PCI/PnP
IRQ15	PCI/PnP

## Peripheral Setup

OnBoard FDC	Enabled
OnBoard Serial Port1	3F8
OnBoard Serial Port2	Diabled
Serial Port2 Mode	N / A
Duplex Mode	N / A
OnBoard Parallel Port	378
Parallel Port Mode	NORMAL
Parallel Port IRQ	7
Parallel Port DMA Channel	N / A
OnBoard IDE	Primary