

AMI Graphical Bios Setup 1994 American Megatrends

<TAB> Move among windows
<ENTER> Select
<ESC> Previous Level
<Alt+H> Help
<Alt+Space bar> Global Exit Choices: Save changes and exit (Default), Do Not Save and exit, or Continue.

SETUP

Standard

Date/Time Use +/- to adjust, arrow keys to move

Floppy Drive A **Not Installed**

Floppy Drive B **1.44 MB 3.5"**

Master Disk Type: USER
 Cyl: 3303
 Hd: 16
 WP: 0
 LZ: 3303
 Sec: 63
 Size(MB): 1705 MB

Slave Disk Not Installed

Advanced

Typematic Rate (Chars/Sec)	Disabled
System Keyboard	Present
Primary Display	VGA/EGA
Above 1 MB Memory Test	Enabled
Memory Test Tick Sound	Enabled
Hit "Del" Message Display	Enabled
Extended BIOS RAM Area	0:300
Wait For "F1" If Any Error	Enabled
System Boot up Num Lock	Off
Floppy Drive Seek at Boot	Disabled
System Boot Up Sequence	C:, A:
System Boot Up CPU Speed	High
External Cache	Enabled
Internal Cache	Enabled
Internal Cache WB or WT	Wr-Thru
Password Checking	Setup
Video Shadow, C000,32K	Enabled
Shadow C800,16K	Disabled
Shadow CC00, 16K	Disabled
Shadow D000, 16K	Disabled
Shadow D400,16K	Disabled
Shadow D800,16K	Disabled
Shadow DC00,16K	Disabled
Shadow E000,64K	Disabled
IDE Multi-Sector Transfer	Auto
Primary IDE 32 bit Transfer	Disabled
Primary IDE Block Mode	Disabled
Primary IDE LBA Mode	Disabled
Secondary IDE Present	None

Chipset

Auto Config Function	Disabled
Cache Read Hit Wait State	3-2-2-2
Cache Write Hit Wait State	1 W/S
DRAM Wait State Select	1 W/S
DRAM Page Mode	Slow
Keyboard Clock Select	7.2 MHz
AT Clock Select	PCLK / 5
Local Ready Delay Setting	Delay 1T
CPU ADS# Delay 1T or Not	No Delay
Alt Bit in Tag SRAM	7 + 1 Bit
Signal LDEV# Sample Time	In T3
ISA Buss Refresh Disable Bit	Slow
DRAM Refresh Method	RAS Only
Divider For Refresh	1 / 1
Video ROM Cache C000, 32K	Disable
System ROM Cache F000, 64K	Disable
LOWA20# Select	Chipset
RC Reset Select	Chipset
IO Recovery Time Select	5 BCLK

Power Management

Power Management Mode Select	Disabled
ALL OTHERS	Disregard