

AMI Graphical Bios Setup

© 1994 American Megatrends

SETUP

Standard

Floppy Drive A	Not Installed	
Floppy Drive B	1.44 MB 3.5"	
Master Disk	Type:	USER
	Cyl:	3303
	Hd:	16
	WP:	0
	LZ:	3303
	Sec:	63
	Size (MB):	1626
Slave Disk	Not Installed	

Advanced

System Keyboard	Present
Primary Display	VGA/EGA
Parity Error Check	Disabled
Extended Bios Ram Area	0:300
Floppy Drive Seek at Boot	Disabled
System Boot Up Sequence	C: , A:
Password Checking	Setup
Video Shadow, C000,32K	Enabled
Shadow C800,32K	Disabled
Shadow D000,32K	Disabled
Shadow D800,32K	Disabled
Shadow E000,32K	Disabled
Internal Cache	Enabled
Internal Cache, Write Mode	Wrt-Thru
External Cache	Enabled
External Cache, Write Mode	Wrt-Back
Video ROM Cache C000,32K	Enabled
System ROM Cache, F000,64K	Enabled
Non-cacheable Area #1 Size	Disabled
Non-cacheable Area #1 Base	Disabled
Non-cacheable Area #1 Type	DRAM
IDE Block Mode	Disabled
Primary Master IDE LBA Mode	Disabled
Primary Slave IDE LBA Mode	Disabled
Primary Ctlr 32 bit Xfer Mode	Disabled

Chipset

System Auto Configuration	Disabled
- Bus Frequency	CLK / 4
- System DRAM Speed	Faster
- DRAM Write Cycle Pulse Time	1T
- DRAM Write Cycle Wait State	1 ws
- Cache Burst Read Cycle Time	2T
- Cache Write Cycle Time	2T
Local Bus Latch Timing	T3
Local Bus Ready (LRDY*)	Sync
16-bit I/O Recovery Time	5 Clks
8-bit I/O Recovery Time	7 Clks

Power Management Setup

IDE Power Down Timeout	Disabled
Power Management Mode	Disabled
All others do not apply	