

## Award Bios Setup (2A4L6D4S)

| HARD DISKS       | TYPE   | SIZE | CYLS | HEAD | PRECOMP | LANDZ | SECTOR | MODE  |
|------------------|--------|------|------|------|---------|-------|--------|-------|
| Primary Master   | : Auto | 0    | 0    | 0    | 0       | 0     | 0      | Auto  |
| Primary Slave    | : None | 0    | 0    | 0    | 0       | 0     | 0      | ----- |
| Secondary Master | : None | 0    | 0    | 0    | 0       | 0     | 0      | ----- |
| Secondary Slave  | : None | 0    | 0    | 0    | 0       | 0     | 0      | ----- |

Drive A : None  
Drive B : 1.44M, 3.5 in.

Video : EGA/VGA  
Halt On : All Errors

## BIOS FEATURES SETUP

|                            |            |                    |            |
|----------------------------|------------|--------------------|------------|
| Virus Warning              | : Disabled | Video BIOS Shadow  | : Enabled  |
| CPU Internal Cache         | : Enabled  | C8000-CBFFF Shadow | : Disabled |
| External Cache             | : Enabled  | CC000-CFFFF shadow | : Disabled |
|                            |            | D0000-D3FFF Shadow | : Disabled |
| Quick Power On Self Test   | : Enabled  | D4000-D7FFF Shadow | : Disabled |
| Boot Sequence              | : C, A     | D8000-DBFFF Shadow | : Disabled |
| Swap Floppy Drive          | : Disabled | DC000-DFFFF Shadow | : Disabled |
| Boot up Floppy Drive       | : Disabled |                    |            |
| Boot up NumLock Status     | : On       |                    |            |
| Boot up System Speed       | : High     |                    |            |
| Gate A20 Option            | : Normal   |                    |            |
| Memory Parity Check        | : Disabled |                    |            |
| Typematic Rate Setting     | : Disabled |                    |            |
| Typematic Rate (Chars/Sec) | : 6        |                    |            |
| Typematic Rate ( Msec)     | : 250      |                    |            |
| Security Option            | : Setup    |                    |            |
| IDE Second Channel Control | : Disabled |                    |            |
| PCI/VGA Palette Snoop      | : Enabled  |                    |            |

## CHIPSET FEATURES SETUP

|                           |              |                          |            |
|---------------------------|--------------|--------------------------|------------|
| Decoupled Refresh         | : Enabled    | Onboard Local Bus        | : Enabled  |
| Video BIOS Cacheable      | : Enabled    | IDE HDD Block Mode       | : Enabled  |
| System BIOS Cacheable     | : Enabled    | IDE Primary Master PIO   | : Auto     |
| External Cache Scheme     | : Write Back | IDE Primary Slave PIO    | : Auto     |
| Combine Alter & Tag Bits  | : Disabled   | Secondary IDE Controller | : Disabled |
| CHRDY for ISA Master      | : Enabled    | Onboard FDC Controller   | : Enabled  |
| Memory Hole At 15Mb Addr. | : Disabled   | Onboard Serial Port 1    | : COM1/3F8 |
| Cache Timing Control      | : Normal     | Onboard Serial Port 2    | : Disabled |
| DRAM Timing Control       | : Normal     | Onboard Parallel Port    | : 378/IRQ7 |
| Fast DRAM                 | : Enabled    | Onboard Parallel Mode    | : SPP      |
| Burst Write               | : Disabled   |                          |            |
| CPU Write Back Cache      | : Disabled   |                          |            |
| Set Turbo pin function    | : Suspend    |                          |            |
| Set Mouse Lock            | : Disabled   |                          |            |

## PNP/PCI Configuration

|                       |           |                           |            |
|-----------------------|-----------|---------------------------|------------|
| PnP BIOS Auto Config  | : Enabled | CPU to PCI Write Buffer   | : Disabled |
| PCI Slot Using INT#   | : Auto    | PCI Master Write Buffer   | : Disabled |
| PCI IRQ Activated By: | : Level   | PCI Master Prefetch       | : Disabled |
| PCI IDE IRQ Map To    | : ISA     | PCI Master Burst Read     | : Disabled |
|                       |           | PCI Dynamic Decoding      | : Disabled |
|                       |           | FRAME Generation          | : Normal   |
|                       |           | Local Memory Detect Point | : Slow     |
|                       |           | PCI Burst                 | : Disabled |
|                       |           | C2P Fast Back-to-Back     | : Disabled |
|                       |           | PCI Master 1 WS Write     | : Disabled |