

OKI-DATA 320 SETUP for DATA LOGGER or Reports

Group	Item	Tear
Printer Control	Emulation Mode	EPSON FX
Font	Print Mode	Utility
Font	DRAFT Mode	HSD
Font	Pitch	10 CPI
Font	Proportional Spacing	No
Font	Style	Normal
Font	Size	Single
Symbol Sets	Character Set-	Set I
Symbol Sets	Language Set	American
Symbol Sets	Zero Character	Slashed
Symbol Sets	Code Page	USA
Rear Feed	Line Spacing	6 LPI
Rear Feed	Form Tear-Off	Off
Rear Feed	Skip Over Perforation	No
Rear Feed	Page Length	11 "
Bottom Feed	Line Spacing	6 LPI
Bottom Feed	Form Tear-Off	Off
Bottom Feed	Skip Over Perforation	No
Bottom Feed	Page Length	11 "
Top Feed	Line Spacing	6 LPI
Top Feed	Bottom Margin	Valid
Top Feed	Page Length	11 "
Top Feed	Wait Time	1 sec
Top Feed	Page Length Control	by Actual Page Length
Set-Up	Graphics	Uni-directional
Set-Up	Receive Buffer Size	64K
Set-Up	Paper Out Override	No
Set-Up	Print Registration	0
Set-Up	Operator Panel Function	Full Operation
Set-Up	Reset Inhibit	No
Set-Up	Print Suppress Effective	Yes
Set-Up	Auto LF	No
Set-Up	Time Out Print	Valid
Set-Up	Auto Select	YES
Set-Up	Graphics Speed (new only)	Low
Set-Up	Centering Position	DEFAULT
Set-Up	Power Saving (new only)	Enable
Set-Up	Power Save Time (new only)	5 min
Set-Up	Time Out FF	Invalid
Parallel I/F	I-Prime	Buffer Print
Parallel I/F	Pin 18 (old only)	+5v
Parallel I/F	Auto Feed XT	Invalid
Parallel I/F	Bi-Direction	Enable